



REVOSYN XP™ – EXTREME - PERFORMANCE MULTI-USE SYNTHETIC INDUSTRIAL OIL

REVOSYN XP™ is a premium, extreme-performance fully synthetic PAO & Ester based lubricant for use in gas/steam turbines, compressors, pumps, bearings and gears.

REVOSYN XP™ has been specifically developed to work in high-temperature and demanding applications and incorporates advanced additive and base oil technology that greatly improves equipment reliability and service life. Our unique additive technology is proven to make equipment run better for longer and more efficiently. REVOSYN XP greatly reduces energy consumption and will increase the mean time between planned/unplanned maintenance and is an ideal replacement for conventional oils operating at high temperature and that rely on their viscosity for protection.

PERFORMANCE ADVANTAGES

- High Film Strength
- Rapidly Separates from Water
- Saves Energy
- Extremely Clean
- Reduces Bearing Vibrations
- Longer Oil Life
- Excellent Corrosion Protection
- Synthetic Solvency
- Compatible with Other Oils
- Fluorescent Under UV Light

INDUSTRIAL

	REVOSYN XP GRADES								
	15	22	32	46	68	100	150	220	320
Viscosity									
cST @ 40°C	15	22	32	46	68	100	150	220	320
cST @ 100°C	3.5	4.5	5.8	7.8	10.2	13.7	18.6	26.8	38.6
Viscosity Index	115	134	134	136	135	138	140	168	168
Flash Point ° C	220	246	246	260	266	270	275	275	275
Pour Point ° C	-59	-53	-47	-38	-38	-30	-30	-30	-30
D-130 Copper Corrosion									
3 hrs. @ 210°F	1A	1A	1A	1A	1A	1A	1A	1A	1A
250 hrs. @ 210°F	1A	1A	1A	1A	1A	1A	1A	1A	1A
D-665 Rust Test									
Fresh Water	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Salt Water	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Specific Gravity	0.825	0.83	0.85	0.855	0.858	0.857	0.864	0.872	0.880