

HIGH - PERFORMANCE

REVOCOMP™

Synthetic Compressor Oil

VISCOSITY GRADES

32 – 150

REVOCOMP™ is a premium, high-performance synthetic lubricant designed to enhance the reliability and efficiency of rotary screw, lobe, and vane compressors. Engineered for demanding, high-temperature applications, **REVOCOMP™** incorporates advanced base oil and additive technology to significantly improve compressor durability and service life.

By reducing wear, oxidation, and deposit formation, **REVOCOMP™** ensures smoother operation, minimizes downtime, and extends maintenance intervals. Its superior thermal stability prevents viscosity breakdown, providing consistent protection even under extreme conditions. Additionally, **REVOCOMP™** optimizes compressor performance by lowering operating temperatures and reducing energy consumption.

For compressors operating at high temperatures or under heavy loads, **REVOCOMP™** is the ideal upgrade from conventional lubricants that rely solely on viscosity for protection.

PERFORMANCE ADVANTAGES

- High Film Strength
- Rapidly Separates from Water
- Reduces Energy Consumption
- Extremely Clean
- Reduces Vibrations
- Longer Oil Life
- Excellent Corrosion Protection
- Synthetic Solvency
- Compatible with Other Oils

TECHNICAL DATA

REVOCOMP GRADE	32	46	68	100	150
VISCOSITY					
cSt @ 40°C	32	46	68	100	150
cSt @ 100°C	5.8	7.8	10.2	13.7	18.6
Viscosity Index	134	136	135	138	140
PHYSICAL PROPERTIES					
Flash Point (°C)	246	260	266	270	275
Pour Point (°C)	-47	-38	-38	-30	-30
Specific Gravity	0.85	0.855	0.858	0.857	0.864
D-130 COPPER CORROSION					
3 hrs. @ 210°F	1A	1A	1A	1A	1A
250 hrs. @ 210°F	1A	1A	1A	1A	1A
D-665 RUST TEST					
Fresh Water	PASS	PASS	PASS	PASS	PASS
Salt Water	PASS	PASS	PASS	PASS	PASS